SuperMax Oil Germany 10W/30





PRODUCT DESCRIPTION

SuperMax Oil Germany 10W/30 is a high performance synthetic gasoline engine oil, formulated with high technology synthetic and mineral base oils with high performance additive combinations. Thanks to its special formulation developed by the help of synthetic technology, it provides better performance than mineral based oils and unique protection under all weather and driving conditions.

ADVANTAGES

- Protection of the engine towards wears and abrasions even at the first starts due to the continuous film layer.
- Good protection of the engine towards wears and oxidation at high temperatures.
- Effective cleanliness due to its modern additive combinations so prevent engine power lost.
- High resistance to oxidation and synthetic base that provide long service life.
- Improved engine power by reducing the wears inside of the engine system.

APPROVALS AND SPECIFICATIONS

• API SL/CF/CF-4/

CHARACTERISTIC PROPERTIES

Viscosity Grade: SAE 10W / 30

Analysis	Unit	Analysis Method	Ideal Values
Density, 15°C	g/cm3	ASTM D 4052	0,8750
Viscosity, 40°C	cSt	ASTM D 445	71,06
Viscosity, 100°C	cSt	ASTM D 445	10,88
Viscosity Index	-	ASTM D 2270	143
TBN	mg KOH/g	ASTM D 2896	7,7
Pour Point	°C	ATM D 92	-30
Flash Point	°C	ASTM D 93	226

STORAGE

Packages should be stored in cool, well-ventilated and covered areas; and their taps should be thightly closed and sealed when not in use. Packages should not be exposed to direct sunlight and avoid rapid climatic changes. Ambient temperature should not exceed 60 °C.

SuperMax Oil Germany 10W/30

Synthetic Technology



SHELF LIFE

Under the appropriate storing conditions suitable to the declared circumstances, maximum shelf life of the products are two years.

HEALTH AND SAFETY

Based on the available information, SuperMax Oil Germany 10W/30 is not expected to produce adverse effects on health when used for the intended application and aligned with the recommendations provided in the; "Material Safety Data Sheet" (MSDS). MSDS's are available upon request through your sales contact office or representative.

When disposing the used product, physical and chemical properties has to be taken into the consideration, and please follow the regional or national regulations